

## MINIATURIZED TERAHERTZ RADIATION SOURCE

FIELD OF THE INVENTION

The present invention [is directed] relates to a miniaturized terahertz radiation source that is based on the Smith Purcell effect[ according to the definition of the species in Claim 1].

5

[It is fundamentally known that, at] BACKGROUND INFORMATION

10

At certain frequencies in the far infrared range, coherent radiation [can] may be generated, for example, by molecular lasers which are pumped by CO<sub>2</sub> lasers. Many of the frequencies and wavelengths of importance to the spectroscopy of molecules and solid bodies [are] may be within the wavelength range extending from 3 mm to 30  $\mu$ m (from 100 gigahertz to 10 terahertz). The use of a microradiation source, which [is] may be tunable within the wavelength range and[ is] implemented on a semiconductor chip of a wafer[, ] for this range of terahertz radiation[, ] and which exhibits sufficient power output within the range of between 1  $\mu$ W and 1 W, [is] may be substantially significant from a technical standpoint for spectroscopic applications in all areas of environmental protection, analytics, and in material characterization in medicine and biology, as well as in chemistry and physics. Another way to generate coherent radiation in the far infrared range is based on the so-called Smith Purcell effect. It provides for generating radiation similar[ly] to the method known from the "free electron laser". Macroscopic electron sources and diffraction gratings having a 100 to 300  $\mu$ m period [are] may be used to generate a coherent radiation field of polarized radiation having up to 1  $\mu$ W power.

15

20

25

30

The [article] reference "Intensity of Smith-Purcell Radiation

EL179952 330

MARKED UP VERSION OF THE SUBSTITUTE SPECIFICATION

in the Relativistic Regime", J. Walsh, K. Woods, S. Yeager,  
Department of Physics and Astronomy, Dartmouth College,  
Hanover, N.H. 03755, U.S., pages 277-279, discusses the theory  
of such Smith-Purcell radiation sources and, additionally,  
5 gives experimental results. [Also, t]The [article  
entitled]reference "A New Source of THz-FIR Radiation" in LEOS  
NEWSLETTER, February, 1999 by J.E. Walsh, J.H. Brownell, J.C.  
Swartz, Department of Physics and Astronomy, Dartmouth  
College, Hanover, New Hampshire 03755-3528 and M.F. Kimmitt,  
10 Department of Physics, Essex University, Colchester, UK,  
January 7, 1999, pages 11-14, [fundamentally  
describes]discusses the design and mode of operation of a  
radiation source in the terahertz region. It may be that  
these[ known] terahertz radiation sources are perfectly  
15 efficient, but they do not yet suffice for many analytical  
applications, and they are not yet miniaturized to a  
sufficient degree.

[For that reason,]SUMMARY OF THE INVENTION

20 The present invention is directed to providing a free electron  
laser, which is miniaturized further extent, [is desired  
as]and may be a more powerful source for analytical  
applications.

25 [The underlying object]Exemplary embodiments and/or exemplary  
methods of the present invention [is, therefore,]are directed  
to [devise]providing a miniaturized terahertz radiation  
source, which is based on the Smith-Purcell effect, on a  
semiconductor chip, using [the known]available additive  
30 nanolithography, which [will]may function as a miniaturized,  
free electron laser, be substantially more powerful than  
existing such radiation sources, and facilitate a  
substantially broader field of application, in particular for  
analytical applications.

35 [The achievement of this objective by the present invention is

delineated in the characterizing part of Claim 1.

Further means for achieving the objective or  
embodiments] Exemplary embodiments and/or exemplary methods of  
5 the present invention are [delineated in Claims 2 through 23.

By] further directed to using additive nanolithography to  
produce such miniaturized terahertz radiation sources, [one is  
able to produce] such that field electron sources having a high  
10 directional beam value may be produced. By employing  
additional miniaturized, electron-optical elements, [such  
as] for example, accelerator grids, focusing lenses, beam  
deflectors, and free-standing metallic rods, the components  
may now be assembled to construct a miniaturized, free  
15 electron laser on a surface of a few 100  $\mu\text{m}^2$  through 10  $\text{mm}^2$ . In  
this context, the electron source has the characteristic of  
emitting electrons at 30 volts, which then possess an energy  
of 30 electron volts. [U] In exemplary embodiments and/or  
exemplary methods of the present invention, using  
20 nanolithography, [ it is possible to control] the second  
characteristic component of focusing and beam guidance of the  
electron beam in parallel to the surface at a finite distance  
to the third component, a metallic grating, may be controlled.  
The vertical position or height of the beam over the metallic  
25 grating may likewise be adjusted by applying deflection  
voltages to micro-miniaturized deflecting plates or wire  
lenses. The diffraction grating, to the extent that is  
possible, up to one millimeter long, [ ] a reflection  
diffraction grating having a grating constant in the range of  
30 0.1 mm to 0.1  $\mu\text{m}$ , may be produced using conventional  
lithography in the manufacturing of electrical connection  
structures for supplying the field electron source, i.e., be  
defined by electron-beam lithography at the highest  
resolutions.

35 [A] In exemplary embodiments and/or exemplary methods of the

present invention, a high-resolution double-resist technique  
and lift-off [are advantageously]may be used. The [present  
approach]exemplary embodiments and/or exemplary methods may  
employ[s] new types of technologies to integrate the electron  
5 source, the beam guidance, and the generation of the  
far-infrared radiation by the flight of the fast electrons  
across the diffraction grating. In this context, given  
standard sources of up to approximately 20,000 volts  
accelerating voltage and an electron beam of 20  $\mu\text{m}$  diameter  
10 over a grating of 100 to 300  $\mu\text{m}$  period, an infrared radiation  
in the far infrared is achieved between 100  $\mu\text{m}$  and one  
millimeter wavelength. This radiation [is]may be produced by  
the image charge, or image potential energy, which oscillates  
in response to the electrons flying past the surface profile  
15 of the grating. The changing spacing between the charges  
produces an oscillating dipole, which may oscillate[s] in  
coherent fashion along the grating. This ensues due to the  
Coulomb interaction of the individual charges on the wires. In  
this context, the entire electrical field may oscillate[s]  
20 coherently in conformance with the individual charges of the  
rods. In this manner, electromagnetic radiation is emitted  
coherently along the entire grating. Its energy transfer from  
the electron beam to the electromagnetic radiation takes place  
virtually losslessly. The polarization may require[s] a  
25 certain displacement current and, thus, a certain power, but  
this [is]may be entirely drawn directly from the beam. [T]In  
exemplary embodiments and/or exemplary methods of the present  
invention, the oscillating dipole charge chain [is]may be  
produced in this manner. [Also novel is]In further exemplary  
30 embodiments and/or exemplary methods of the present invention,  
integration of the electron guidance on a chip, and the direct  
coupling to the grating having a high spatial resolution, in  
the manufacturing process[. Just as novel is that]is  
provided. In further exemplary embodiments and/or exemplary  
35 methods of the present invention, micro-miniaturization [is  
making possible]may allow for the use of low-energy electrons

having energies of between 10 and 1000 eV. [It is also possible to generate]Further exemplary embodiments and/or exemplary methods are directed to generating up to 10 kV of electrons on the chip and to implement the guidance by using  
5 miniaturized electron-optical components, such as micro-lenses and deflecting elements.

[W]In further exemplary embodiments and/or exemplary methods of the present invention, when using such high-energy  
10 electrons, radiation may also be generated for short wavelengths ranging from middle infrared to the visible spectral region. By manufacturing on a common substrate, one ensures direct coupling to the grating via the shortest distance to the source, and the manufacturing of the grating  
15 and the source on the same chip. In this manner, in further exemplary embodiments and/or exemplary methods, the path of rays of the electrode configuration, which in [the]a conventional design, [is]may be up to one meter, is reduced to less than 1 mm to 10 mm length. Moreover, a very highly  
20 coherent and local light source [is]may produced, which benefits the temporal and spatial coherence of the radiation.

[B]In exemplary embodiments and/or exemplary methods of the present invention, because the entire electron path is shortened to a greater degree, it [is]may be no longer  
25 necessary to use extra-high or high vacuum in the radiation room. It may suffice[s] to cover the system by a window etched in silicon using a flipchip bonding technique. This window [is]may be closed by a continuous membrane of silicon, thereby rendering possible a hollow space. The up to 10  $\mu\text{m}$  high  
30 component [is]may be easily accommodated in the hollow space. [Typically, i]Into a silicon wafer of 250  $\mu\text{m}$  thickness, one may etch[es] windows of a few millimeter diameter, which are sealed by a membrane having a thickness of 10  $\mu\text{m}$  up to 100  $\mu\text{m}$ . This [renders possible]may render a stable mechanical  
35 encapsulation of the miniaturized component. [However]In exemplary embodiments and/or exemplary methods of the present

invention, it can also be manufactured micromechanically, in millimeter dimensions. In this context, the required vacuum is approximately 0.01 Torr. In this case, the average free path length of the electrons in this gas of reduced pressure is as large as the beam length of the miniaturized component. This can eliminate[s] the need for a pump configuration[, which is a significant advantage]. The component can be packaged as a ready-made, sealed element and [ ]connected. In this manner, [it is possible to produce] a terahertz radiation source may be produced, i.e., a millimeter and submillimeter radiation source on a semiconductor chip. Through appropriate wave guidance, this radiation source can be linked to further applications.

[Further advantages, features, and possible applications of the miniaturized or micro-miniaturized terahertz radiation source, in particular its design and mode of operation, may be derived from the following description in conjunction with the exemplary embodiments depicted in the drawing.

The present invention shall now be elucidated on the basis of exemplary embodiments depicted in the drawing. The terms and assigned reference symbols employed in the appended reference symbol list are used in the Specification, the Claims, the Abstract, and in the drawing.

In the drawing:

Figure 1            ]BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a plan and side view of a fundamental design of a miniaturized terahertz radiation source based on the Smith Purcell effect[;].

Figure 2[           illustrates]shows an encapsulation having a silicon membrane structure for maintaining the necessary vacuum during operation[; and].

Figure 3[ depicts] shows a two-chamber membrane covering of the miniaturized, free electron laser.

#### DETAILED DESCRIPTION

5 Figure 1 schematically depicts the electrode design for a miniaturized, free electron laser in a plan view and side view. The individually illustrated elements [are] may also be produced using a[ known] n available additive nanolithography method. Shown both in the plan view as well as in the side  
10 view, the individual elements of the miniaturized terahertz radiation source are illustrated in the following sequence. First, field emitter tips 1 are shown to the left. They are linked via electrical terminals or connections 2 to a controllable voltage source 3 and, on the other hand, to an  
15 electrostatic lens 4, composed here of three electrodes. The left electrode is the extractor or the first anode of the electron source. Shown in the middle are beam deflectors 5 having connections 6, to which optical and/or electron-beam lithography and a deflection voltage are applied. Beam  
20 deflector 5 is followed by a grating 7 of metal. Electron beam 9, having been deflected by beam deflector 5, passes through this grating and strikes here as an electron beam, without being deflected 10, upon a second anode 8.

25 Figure 2 shows [one] an exemplary variant of an encapsulation. This design enables the electron source, here in the form of field emitter tips 1, electrostatic lens 4 for focusing electron beam 9/10, beam deflector 5 for deflecting the beam in the horizontal and vertical direction, grating 7 of metal  
30 having an underlaid reflector to be constructed in integrated fashion, using mix-match technology employing additive nanolithography on an insulating substrate having a terahertz reflection base\_[ ] in the grating region, on metal conductor connection structures, which are prefabricated using electron  
35 beam or optical lithography, and to be imperviously encapsulated in a vacuum 13 using a technology which is

transparent to terahertz radiation. This design enables electron beam 9 emerging from field emitter 1 to be focused through miniaturized wire lenses 4, to be directed through integrated deflecting plates 5 relatively to the position of grating 7, and to be positioned, thereby generating terahertz radiation, whose intensity and wavelength may be varied and selected. Field emitters, i.e., field emitter tips 1 are linked via an electrical terminal connection 2 to a controllable voltage source 3 and, moreover, via an electrical connection 2 to the middle electrode of electrostatic lens 4. The left electrical electrode of lens 4 is the first anode of the electron source and, together with a terminal of controllable voltage source 3, is connected to ground, as is also the electrode of electrostatic lens 4 situated on the other side of the middle electrode. The field electron source having field emitters 1 is a wire constructed, using additive nanolithography, out of readily conductive material having stabilizing series resistance, and [is]may be designed such that electron beam 9 emerges in parallel to the surface. This means that the wire is manufactured, using a computer-controlled deposition lithography, in a straight or curved design, to end freely over the surface of the conductor path structure. The field electron source has a punctiform design. On its field emitter tips (1), a material having a low work function is deposited using additive nanolithography, so that electrons are emitted already in response to relatively low voltages.

[One]An exemplary variant of the design provides for mounting an accelerator grid as a beam deflector 5, in the form of a free-standing electrode composed of two cylindrical rods or a standing wire ring, behind the field electron source having field emitters 1. The [intention here is for the ]electrons [to]may thus be accelerated and directed into subsequent, additionally constructed round multipole lenses and/or cylindrical lenses, so that the propagating electron beam 9 is



additionally deflected over subsequent diffraction grating 7 at a homogeneous distance to the surface. The focusing and beam-guidance lenses, which are implemented by additive nanolithography on the metal connection structure produced using electron-beam lithography or optical lithography, are constructed, using this technology, to produce a diffraction grating having a length of approximately 1 mm to 1 cm, with grating periods of 0.5 to 10  $\mu\text{m}$ , depending on the wavelength of the terahertz radiation to be emitted.

[One] An exemplary variant of the design may also provide[s] for a side-by-side configuration of a plurality of electrically isolated diffraction gratings, which may be activated by selecting various sources, enabling various emitted wavelengths to be chosen.

The radiation from electron source is retained at a constant level by a control circuit, in particular by a controllable voltage source 3, and electron beam 10 propagating over grating 7 is then picked up by a second anode 8, which is used as a collecting anode electrode.

Between the second earth electrode of electrostatic lens 4 and second anode 8, a field is applied, which may be used to alter the electron velocity along the grating. This [is] may be used for precisely adjusting the wavelength and also for generating a frequency spectrum.

Another exemplary embodiment of the design of the miniaturized, i.e., microminiaturized terahertz radiation source, based on the Smith-Purcell effect, is shown in Figure 2. By providing encapsulation using a silicon membrane structure, the required vacuum 13 may be maintained for operating the laser. The emitted laser THz radiation 15 is radiated to the outside through a membrane window 14. The radiation emitter, constructed on a chip of silicon 11 and

composed of the field emission source, optics, grating and anode, is covered in this exemplary embodiment by membrane window 14, which is made of silicon 11, as [is]may be the entire covering chip 16. The thus constructed radiation emitter [is]may be evacuated in a vacuum system, prior to the bonding, to a pressure of  $10^{-4}$ , which suffices for one millimeter average free path length. The hollow space [is]may subsequently be sealed in the vacuum by thermal bonding, without short-circuiting the voltage supply. Membrane windows 14 in covering chip 17 [are]may be treated using reflection-reducing layers, so that a maximum transmission through window 14 is attained for the frequency range of the emitted radiation.

[C]Further, configured underneath the grating region [is]may be a THz radiation reflector in the form of a metal layer or arrangement of grating rods, having a defined spacing of a suitable period, of magnetic or non-magnetic materials, so THz radiation 15, which exits grating 7 in the direction of the substrate, [is]may be sent back through the grating with the highest possible reflectance, thereby strengthening the intensity of the emitted radiation. Implementing a beam guidance over grating 7 at a defined distance [makes it possible to vary]can may allow variation of the intensity of the radiation source. This means that by employing deflecting element 5 before the grating, the radiated intensity may be modulated in response to the application of an [a.c.]alternating current voltage to this deflecting element. In this manner, the radiation may be directly generated in modulated form for spectroscopic purposes for lock-in measuring techniques. The same lock-in modulation may also be provided by modulating the extraction voltage at field emitter tip 1.

For certain applications, [it is beneficial to supplement ]the voltage source may be supplemented by installing a

monochromator on an overlying surface. Such a monochromator  
[is]may be constituted as a nanometer structure or micrometer  
structure that acts on this region, so that beams generated  
with a different wavelength exit the radiation source in  
5 different directions. In this manner, by switching over the  
electron energy, which, in the electrostatic system in  
accordance with the electrostatic principle, may always  
yield[s] the same focusing and, thus, constant operating  
conditions, radiation of different frequencies may be  
10 generated, and the radiation source may be electrically tuned  
for different applications.

Between focusing lens 4 and the end of grating 7, one variant  
provides for applying an electrical field, in which, at the  
15 end of the grating, an additional electrode is positioned,  
through which voltage may be applied to accelerate or  
decelerate the flying electrons. This makes it possible to  
compensate for the energy loss experienced by the electrons  
when flying past grating 7. Grating 7, over which electron  
20 beam 10 propagates, [is]may be subdivided into regions which  
are disposed in parallel to the beam direction, in which  
different grating constants are implemented. The horizontal,  
electrostatic beam guidance, effected by electrodes positioned  
in parallel to grating 7 and, respectively, by a plurality of  
25 electron sources, one of which is assigned to the individual  
region, [now makes it possible]may allow for the emitted  
radiation to be implemented as radiation that is switchable in  
its wavelength.

30 The grating constant of the grating [varies]may vary  
transversely to the beam direction, so that the beam guidance  
may be varied over the grating by deflection fields or by  
deflecting plates, which surround the grating all around, and  
are positioned behind the focusing lens, such that a region  
35 having a different grating constant may be selected for  
emitting the wavelength of the radiation. Designing the

grating as a "chirped grating", i.e., as a grating having a variable grating constant, enables the wavelength to be adjusted in continuous fashion.

5 The intensity of the terahertz radiation source is controlled by installing an electrostatic plate, which is transparent to THz radiation, below and above the grating, thereby enabling the intensity to be locally selected, or selected with respect to particular locations. This [is advantageously] may be  
10 achieved by designing these electrostatic plates to include regions of different potentials, i.e., by providing separately adjustable strips.

Figure 3 shows another exemplary embodiment, where two  
15 membrane windows 14 are provided in covering chip 17. As in Figure 2, [it can also be discerned here quite clearly that ]covering chip 17 [is] may be insulated from the electrodes and the electrode connections by an insulator of silicon 16. At the same time, this is also constituted of bond region 7 for  
20 providing hermetic sealing when encapsulating the arrangement. The construction includes, in turn, the substrate of silicon 11 having a silicon dioxide layer 12. Positioned thereon are field emitter 1, lenses 4, grating 7 and second anode 8. [Here, again, t] The first anode is the left electrode of  
25 electrostatic lens 4. Also positioned, in turn, is grating 7 of metal, out of which the emitted terahertz radiation 15 emerges. Electron beam 10 impinges, without deflection, on second anode 8 having electrical connection 2. The one membrane window 14 is provided with a lens 19 for focusing THz  
30 radiation 15. Due to the specially formed covering chip 17, a vacuum 13 [is] may be provided in both chambers 18, 18'; a getter pump[ (not shown)], including its material, may be set in operation in second chamber 18' by a one-time activation in response to current flow, to bring the entire volume of both  
35 chambers to the required operating pressure.

In a further exemplary variant[ (not shown)], ionic getter materials, capable of being activated by the electrical connection, are applied to the chip, next to the Smith-Purcell element. These materials [are]may be used for pumping out the bonded and encapsulated structure. Such a manufacturing, employing additive nanolithography on metal conductor-connection structures, which are prefabricated by electron beam lithography or optical lithography, may include integrated grating structures on an insulating substrate, [in particular]such as silicon oxide, and a THz underlaid reflector integrated in the grating region, renders possible a component which may be used and set up in any position as a THz radiation source in modular form.

[

## Reference Symbol List

	1	field emitter (tips)
	2	electrical terminal or connections
5	3	controllable voltage source
	4	electrostatic lens
	5	beam deflector or deflecting plates
	6	electrical connections for beam deflectors
	7	metal grating
10	8	second anode
	9	electron beam
	10	electron beam without deflection
	11	silicon (Si)
	12	silicon dioxide (SiO <sub>2</sub> )
15	13	vacuum
	14	membrane window of silicon
	15	emitted terahertz radiation
	16	insulator or bond region for vacuum-tight encapsulation of the arrangement
20	17	covering chip
	18, 18'	chambers
	19	lens for focusing the THz radiation

Abstract]

ABSTRACT OF THE DISCLOSURE

A miniaturized terahertz radiation source based on the  
5 Smith-Purcell effect is provided, in which, from a focused  
electron source, a high-energy bundle or beam of electrons is  
transmitted at a defined distance over a reflection  
diffraction grating composed of transversely disposed grating  
rods, so that, in response to oscillating image charges,  
10 electromagnetic waves of one wavelength are emitted, the  
wavelength being adjustable as a function of the periodicity  
of the lines and of the electron velocity. The elements of  
the radiation source, such as field emitter [ (1) ],  
electrostatic lens [ (4) ], beam deflector [ (5) ], grating [ (7) ]  
15 of metal, and a second anode [ (8) ], are integrated on a  
semiconductor chip using additive nanolithographic methods.  
The field electron source is constructed to project, as a  
wire, out of the surface, using additive nanolithography, and  
is made of readily conductive material having stabilizing  
20 series resistance. The wire is constructed, using  
computer-controlled deposition lithography, in a straight or  
curved, free-standing design. In its surface area, the base  
material bears a conductor structure for the electrical  
terminals and connections [ (2) ], including controllable  
25 voltage sources [ (3) ] for supplying the field emitter tips [ (1) ],  
lens [ (4) ], and control electrodes [ (5, 8) ]. The  
terahertz radiation source is designed to be a powerful  
component that [is] may be available in modular form and  
[is] may be usable in any spatial situation.

30 [ ]